

DoP - DECLARATION of PERFORMANCE TECNOCOAT P-2049 EL
Construction Products Regulation n°305/2011

Manufacturer	TECNOPOL SISTEMAS, S.L.
Adress	Finlàndia, 33 08520 Les Franqueses del Vallès · Barcelona · Spain
Contact	t +34 935 682 111 · f +34 935 68 0211 · info@tecnopol.es

Product/system identification	TECNOCOAT P-2049 EL
Use	liquid applied roof waterproofing, based on 100% pure elongable polyurea
Area code	System 4
Norm and certification	EN ISO 527-3
Control laboratory	LGAI TECHNOLOGICAL CENTER S.L. APPLUS
Revision date	10-10-2016

DECLARED PERFORMANCES

Minimum thickness	1,5 mm
Tensile strength at 23°C ISO 527-3	23,19 MPa
Elongation at 23°C ISO 527-3	≥600%
Elongation at -40°C ISO 527-3	≥350%
Hardness Shore A DIN 53.505	>75
Initial dry time at 23°C	13-25 secs.
Roof slope	≥0°
VOC (volatile organic compounds)	0
Fire reaction	Euroclass F

The performance given for this product or system, are agreed with the declared performance.
 This declaration of performance is issued under the responsibility of the manufacturer listed.

