





DoP - DECLARATION of PERFORMANCE TECNOTOP 2C

Construction Products Regulation na305/2011

Manufacturer

TECNOPOL SISTEMAS, S.L.

Finlàndia, 33 08520 Les Franqueses del Vallès ·
Barcelona · Spain

Contact

t +34 935 682 111 · f +34 935 68 0211 · info@tecnopol.es

Product/system identification TECNOTOP 2C

Use protection for a waterproofing membranes, and for flooring

Area code System 3

Norm and certification#1 ETAG# 005 -LARWK- liquid applied roof waterproofing

kits(EOTA) ETA 11/0357

Control laboratory#1 Instituto de Ciencias de la construcción Eduardo Torroja

(EOTA member)

Norm and certification#2 BBA 16/5340 Approval Inspection Testing Certification

Control laboratory#2 British Board of Agrément

Revision date 10-10-2016



DECLARED PERFORMANCES

Density at 23° C ISO 1675

1,20 g/m3

Solid contents ISO 1788

71%

Pot life at 23°C

>1 hour

Elongation at break at 23°C ISO 527-3

35%

Adherence to concrete at 23°C

>2 MPa

Tack free time at 23°C

2 hours

Complete cured time at 23°C

7 days

Repaint time range at 23°C

4-48 hours

The performance given for this product or system, are agreed with the declared performance. This declaration of performance is issued under the responsibility of the manufacturer listed.



Tecnopol QA/QC Department

NOTICE: While all the information presented in this document is believed to be reliable and to represent the best available data on these products, do not constitute sales specifications. The product properties may be changed without notice. NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. Liability of Tecnopol Sistemas and its affiliates for all claims is limited to the purchase price of the material. Products may be toxic and require special precautions in handling. User should obtain detailed information on toxicity, together with proper shipping, handling and storage procedures, and comply with all applicable safety and environmental standards. No freedom from any patents or other industrial or intellectual property rights is granted or to be inferred.